

Windows » PVC windows » IGLO EXT



**IGLO EXT**

The system opens outwards. Modern design and great thermal insulation parameters mean a warmer house and lower bills.

Features

1. Opening outwards.
2. Attractive design.
3. As standard, hidden hinges for windows; door hinges (surface hinges) for balcony doors.
4. Wide range of coloured foils finishes and textures
5. Great thermal parameters that ensure superb energy efficiency savings thanks to the optimum structure and EPDM seal.
6. Frame structure with full reinforcement.

**Technical data**

Profile	5-chamber profiles made exclusively from A-class Virgin grade Upvc, with installation depth of 70 mm.
Glass	Glazing thickness up to 40 mm. as standard, double glazed package of coefficient of heat transmission $U_g = 1,0 \text{ W}/(\text{m}^2\text{K})$ according to PN-EN674. The possibility to apply sealed units of up to $U_g = 0,6 \text{ W}/(\text{m}^2\text{K})$ coefficient. The possibility to apply glass with enhanced sound insulation, laminated (safe and anti-theft), ornamental, solar control and sandblasted.
Spacer frame	Standard spacer bar is made from, steel galvanized Optionally Swisspacer Ultimate available in various color options.
Fittings	Turn-only fittings - MACO, DM25 espagnolettes.
Gaskets	The window is equipped with a system of double draught seals -external, internal EPDM available in black and grey as standard, a seal filling the bottom fitting groove
Colour range	The system is available in wide color range of Renolit foils based on a white profile
Reinforcement	Full steel reinforcement in the frame, in the sash - steel channel-shaped reinforcement.
Thermal isolation	$U_w = 0,89 \text{ W}/(\text{m}^2\text{K})^*$

\*For a window 1230x1480 mm - calculation method