

Terrace systems » Tilt and slide PSK » IGLO5 PSK



Tilt and slide balcony door PSK Iglo 5

Perfect solution that ensures big access to daylight both in small and big room, maintaining great thermal insulation at the same time.

Features

- 1. Design that reflects innovativeness and unconventionality.
- 2. High safety level guaranteed by the application of four anti-burglary bolts in standard.
- Possibility to customize the interior as the result of the wide range of colours;
- 4. Very good thermal parameters ensure heat saving thanks to optimal structure and EPDM sealing.
- 5. Good parameters in sound insulation that guarantee acoustic comfort.
- 6. The possibility to execute in the so-called thin wielding technology (V-Perfect), that allows to connect the profiles perfectly and it guarantees better clamp and wielding control, and, as a result, very good parameters in the resistance tests of the corners (Iglo 5 Classic).

Technical data

Fittings The possibility to apply automatic fitting that supports tilt closing. Four anti-burglary bolts in standard.

Sound isolation -

One-chamber glass package with thermal transmittance Ug=1,0 $W/(m^2K)$ according to the PN-EN674 norm in standard. The possibility to apply Glass three-glass package with Ug = 0,7 $W/(m^2K)$. Maximal glazing thickness up to 36 mm. The possibility to apply glasses with enhanced sound insulation, tempered, safety, anti-burglary, ornament or solar protective.

Colour range The system is available in Renolit foil colours on white or brown core.

Profile 5-chamber frame and sash profiles made exclusively of prime material in A-class with installation width 70 mm.

Reinforcement Frame reinforcement – full steel (closed). In the full reinforcement, anti-burglary bolts are screwed to the steel. C-shaped reinforcement beam in the sash.

The door is equipped with a system of double sealing; external, internal made

Gaskets of EPDM, available in black, grey colours. Gasket that fullfills the bottom fitting

ditch in standard.

 $\mbox{Spacer frame} \begin{tabular}{ll} \mbox{Steel galvanized spacer frame in standard. Optionally Swisspacer Ultimate available in various colour options. \end{tabular}$